

REA 18kW Dry Saturated Steam Generators – Heavy duty professional

Ideal for cleaning, sanitising and degreasing of all types of equipment and surfaces in the Food Manufacturing and Engineering Industries.

REA S18E

REA Special 2



Tools listed separately

Technical Specifications of REA 18kW Steam Generators		
Model Name	S18E*	Special 2
Power Supply	400V /28A/ 50Hz	400V /28A/ 50Hz
Power	3-phase 18kW	3-phase 18kW
Steam Production	30 kg/hour	30 kg/hour
Temperature in boiler	188°C	188°C
Temperature at nozzle	150°C	150°C
Bar of Pressure	12	12
Start up time	4 minutes	4 minutes
Water Tank Capacity	25 lt	100 lt
Water Consumption	30 lts/hr	30 lts/hr
Water Indicator	Yes	Yes
Detergent Tank	10 lt	10 lt
Detergent Indicator	Yes	Yes
Adjustable Detergent Mixer	No	Yes
Standard Hose Length	6 mt	6 mt
Maximum Hose Length	12 mt	12 mt
Electrical Cable Length	10 mt	10 mt
Control Handle / Control Panel	Analogue 12V / 24 V	Digital 12V / 24 V
Markings and Certifications	CE - PED - IPX 5	CE - PED - IPX 5
Vacuum	No	Socket for Vacuum 057 operated from the control handle
Weight	165 kgs	165 kgs
Dimensions in cms	L128 x W745 x H102	L128 x W745 x H102
Body	Stainless steel (AISI 304)	Stainless steel (AISI 304)
Functions Selected from the Control Handle	1. steam only 2. steam and detergent	1. steam only 2. steam and detergent 3. steam and water
Steam Technology Solutions Pty Ltd 07 3715 7731 1300 761 962 www.steamtech.com.au info@steamtech.com.au	*Variation - No detergent S18E ND - 100 lt water tank	4. steam, detergent and vacuum 5. steam and vacuum 6. vacuum